

# Certificate of Technical Specifications

ceusa

PRODUCT: ITALIAN DAYS CORNER MIX LUX  
 FORMAT: 99,5X99,5x7,4MM CONTAINS: 12 Pieces 0,12 m<sup>2</sup> 1,29 SQFT GROUP: Bla

Technical Characteristics	ISO	Req.	Unit	Specification
DIM. VAR. IN REL. W. OF THE GREATER SIDE	10545-2	±0.90	mm	±0.90
DIM. VAR. IN REL. W. OF THE MINOR SIDE	10545-2	±0.90	mm	±0.90
THICKNESS VARIATION	10545-2	±0.40	mm	±0.40
STRAIGHTNESS OF THE GREATER SIDE	10545-2	±0.80	mm	±0.80
STRAIGHTNESS OF THE MINOR SIDE	10545-2	±0.80	mm	±0.80
DEVIATION FROM ORTHOGONALITY OF THE GREATER SIDE	10545-2	±0.80	mm	±0.80
DEVIATION FROM ORTHOGONALITY OF THE MINOR SIDE	10545-2	±0.80	mm	±0.80
CENTRAL DIAGONAL CURVATURE DEVIATION	10545-2	±0.80	mm	±0.80
DEVIATION OF THE CURVATURE OF THE SIDES	10545-2	±0.80	mm	±0.80
DEVIATION OF THE CURVATURE OF THE SIDES	10545-2	±0.80	mm	±0.80
BENDING OVER DIAGONAL	10545-2	±0.80	mm	±0.80
QUALITY OF SURFACE	10545-2	≥95	%	≥95
WATER ABSORPTION	10545-3	≤0.50	%	≤0.50
RESISTANCE TO BENDING	10545-4	≥35	N/mm <sup>2</sup>	≥35
BREAKING STRENGTH	10545-4	≥1300	N	≥700
CLASS OF USAGE	-	-	USE:	4
THERMAL SHOCK RESISTANCE	10545-9	-	-	-
LINEAR EXPANSION COEFFICIENT X 10-6	10545-8	-	C-1	-
MOISTURE EXPANSION	10545-10	-	mm/m	≤0.30
GRAZING RESISTANCE	10545-11	Required	-	OK
RESISTANCE TO CHEMICALS	10545-13	Minimum Class GB	-	GA
RESISTANCE ATTACKS ACID/ALKALINE	10545-13	Specify	-	GLB
SURFACE RESISTANCE TO STAINS	10545-14	Minimum Class 3	-	4
COEFFICIENT OF FRICTION WET	NBR 16919	Specify	-	<0.4
CHANGES IN HUE				V3

Note: Product in accordance with the ABNT NBR 13006 standard  
 Evaluation of reaction to fire (NBR15575): Class I (non-combustible)  
 USE 4 - All residential areas.

  
 Andre Bez Batti  
 Responsável Técnico